

Nat. Hazards Earth Syst. Sci. Discuss., author comment AC3
<https://doi.org/10.5194/nhess-2021-161-AC3>, 2021
© Author(s) 2021. This work is distributed under
the Creative Commons Attribution 4.0 License.

Reply on RC2

Manuel Andres Diaz Loaiza et al.

Author comment on "Development of damage curves for buildings near La Rochelle during storm Xynthia based on insurance claims and hydrodynamic simulations" by Manuel Andres Diaz Loaiza et al., Nat. Hazards Earth Syst. Sci. Discuss.,
<https://doi.org/10.5194/nhess-2021-161-AC3>, 2021

The authors present the results of a coupled Delft3D+SWAN hindcast simulation of extratropical storm Xynthia and present damage curves derived through analysis of the hindcast results in combination with insurance claims data near La Rochelle, France. Through their results, the authors demonstrate that grid/mesh resolution can impact the shape of the resulting damage curves, and that the best explanatory variables for damage are water depth and total hydrodynamic force. The authors suggest in their concluding statements that their work may have broad application to assess damage from future events along the French Atlantic coast, but subsequently provide numerous qualifiers on their work that contradict the preceding claim.

This certainly is an interesting piece of work and I believe it has a strong foundation that can be improved upon in subsequent revisions. While the technical focus is appropriate, I found the current version of the manuscript lacking in a few substantial ways. The deviation from standard practice when developing damage curves notwithstanding, the work shows promise and will be an excellent contribution to the published literature with a few substantial improvements to the analyses and manuscript.

Response: Dear Bret, thank you for your comments, we will certainly improve the manuscript with your comments and the other reviewers/participants on the interactive discussion forum. Down below I will answer point by point your comments.

My general recommendations for improving the manuscript are as follows:

- Improve the organization of the manuscript, especially the early sections of the text. There should be a clear and distinct progression from the introduction to the methods. The methods section contains information about the study area and the storm, which would be better presented in the introductory section of the manuscript. The organization of the methods section is inconsistent and could be improved to flow more logically. For example, there is discussion of the models and model setup in multiple places of 2.1, 2.2, and 2.3. Furthermore, this section begins with (cf. 2.1) a detailed discussion of the particular storm event without first describing the storm or the models. Section 2.2 could be combined with another section in the reorganization. One may also argue that the validation results belong in the "Results" section, not in the

method section. Section 2.4, albeit brief, is appropriately placed and contains helpful information. I will, however, note that use of the term "damage level x " in line 124 is somewhat inconsistent with your chosen approach and terminology. Also, that " x " is not the damage ratio but rather the value of the conditional variable (the hazard) for a specific damage ratio increment. Therefore, you likely need a subscript on P such that $P_i(x)=...$ gives the probability of experiencing hazard value " x " for damage ratio value " i " and so on. I'm sure that is what you did in the analysis, but the typesetting of Equation 2 and the corresponding text should be improved.

*Response: We think that the best way to structure the paper is to start mentioning the economic damages and the damage functions development, instead of focusing on the storm Xynthia and the hydrodynamic simulation. Indeed, it is mentioned below that we should give more importance on the damage function development than the hydrodynamic simulations. Nevertheless, due to your comment and those from reviewer 1, we decide to include another paragraph about **"the common way of developing damage functions? what do the previous researchers have done? what are the main conclusions of their works?"** and move some part from the conclusions to the discussion. A short sentence with reference on the introduction related with the Xynthia storm was added too*

Related with the explanation of the damage function, we agreed that now is not clear the explanation. In the new version, the text will be as follows: "where $P(x)$ is the cumulative probability of the damage ratio with values between 0 and 1, and x is the hydrodynamic variable, Φ is the standardized normal distribution, μ is ...".

2) The analyses, while well intentioned, are not particularly robust in their presentation. For example, there is no quantitative assessment of model errors or bias in the prediction of either water levels or wave heights. Simply plotting predictions and measurements and saying the agreement is "good" does not inspire confidence, particularly when the disagreement between the two for wave heights appears to be quite substantial. As a second example, there really is not enough information provided relative to the development of the damage curves given its prominence in the title of your manuscript. So while the content of the existing manuscript is strong, it is simply short on details and could benefit from an expanded discussion in many places (a few of which are noted below).

Response: In the newer version we are including a goodness of fit indexes (RMSE, Pearson coefficient and RRMSE), between the observed tide and waves values and we compare these values with others values obtained in the literature.

- There is a duality in the manuscript that I am having a hard time reconciling, particularly given point #2 above (lack of detail). There is a significant emphasis placed on the influence of grid resolution on the resulting damage functions. However, there is not enough supporting detail provided for these grids/meshes. Given that there is similarly a lack of detailed information regarding the development and application of the damage curves (additional comments below), this leaves the manuscript lacking in technical details as mentioned earlier. While the impact/influence of the grid resolution is noteworthy, it does not appear to be the focal point of the paper (not in the title) so I would suggest minimizing its relevance and adding much more detail to the damage curve discussion. Alternatively, if the authors would prefer not to expand the discussion of the damage curves and instead reorient the focus of the paper to one associated with the grid resolution, then consider greatly expanding details regarding the features and characteristics of those grids and perhaps modify the manuscript title accordingly.

Response: Yes, indeed the idea of the paper is not to focus on the mesh resolution. Instead, in the current paper we investigate three different bathymetry/topography data sets, each with its own resolution and quality.

4) I have some reservations about your analysis methodology. Not to say that it is in any way “wrong” but it does suffer from a lack of explanation (again, just my opinion). I would like to see some detailed description of the building archetypes considered in this analysis. Are all buildings considered to be of the same archetype (I assume so because there is no differentiation in the results)? Can you provide more details beyond “stone masonry” such as number of floors/heights, foundation types, age of structures, roof types/materials, etc.? Without the qualifiers, I think it would be very easy for someone to misapply your methodology.

Response: For this initial part of point 4 unfortunately no more information was available (such as the types of structures, number of floors and damage stages), even more the location of the claims due to the new European data protection policy were masked, making the extraction of the hydrodynamic variables an iterative process between the insurance company and TU-Delft.

Also, I would like to see a better presentation of the explanatory variable (hazard) values for the damage curves. I know that you have presented them graphically in the appendix, but it would be valuable to also list the means and standard deviations (likely for only one grid) of those variables/variable groups. Finally, can you add some discussion regarding potential weaknesses of your chosen “damage ratio” approach to representing damage? There are many weaknesses with using this as a substitute for the more common “damage state” because the damage ratio does not correct for valuation based on location among other weaknesses. As another example, “insured value” is often a personal/elective choice made by the homeowner and there is bound to be substantial inconsistency in what one chooses to insure their property for. To expand a bit further, a low damage ratio value may be the result of minimal damage or a very high insured value. Therefore, the damage ratio is sensitive to two metrics, one of them choice-based, as opposed to a traditional damage state classification which, while somewhat objective, focuses only on the severity of damage to the property. My primary concern here is founded upon the fact that nearly one-half of your 423 reported claims have an assigned damage ratio <0.1 (cf. Figure 1). Finally, in a traditional damage/fragility analysis one would also consider structures with no damage. I do not recall any mention of non-damaged structures in your analysis. Therefore, the resulting damage curves may very well be biased.

Response: Regarding the means and the standard deviations we believe that in order to maintain an adequate extension of the paper we should not include another table since they are already displayed in the box-whisker plots. For the newer version, we add a paragraph commenting on the uncertainty that the quality of the claims add to the analysis, since unfortunately cannot be assessed. As you commented, the insured value, or the economic claim can be exaggerated by the owners. About the 423 reported claims and the distribution of their damage ratio, as you mentioned, is a matter that involves the quality of the claims itself, but also the hydrodynamics conditions, that are particular for every case. In the case of La Rochelle and more noticeable for Ille du Re, there are structures at the foreshore, but usually the more densely populated areas are some hundreds of meters inland where elevation is higher and then less damages is expected. Finally, including non-damaged structures indeed will add value into this kind of analysis; however we do not possess this data.

Here are some additional comments that address specific items in the manuscript...

Line 30/Figure 1: recommend normalizing the ordinate values by the total number of claims so that you can report these in terms of their true “frequency” instead of simply

counts. If not, please edit the axis title as these are not frequencies.

Response: Yes, the figure is changed in the new version.

Line 38: the introduction in its current form is significantly lacking in terms of a thorough review of pertinent literature on damage functions derived from coastal hazard models (e.g., Masoomi et al., 2019 and many others), lacks an orientation to the study area, and does not thoroughly describe the storm event. I would recommend adding:

- much more background on relevant literature

- a detailed description of study area with location map, exposure/vulnerability to extreme events, hydrodynamic setting, etc.

- more information on the history and characteristics of Xynthia

Masoomi, H., van de Lindt, J.W., Do, T.Q., Webb, B.M. 2019. Combined wind-wave-surge hurricane-induced damage prediction for buildings. *Journal of Structural Engineering* 145(1).

Response: Yes, this reference and others, both together with a better explanation for the damage functions and Xynthia storm is added.

Line 41: minor comment but use consistent typesetting of "Delft3D" throughout the document.

Response: Yes, thank you is amended.

Line 48/Figure 2: any reason why there is a font change in this graphic? Was that intentional?

Response: Fonts on the figures are checked and corrected

Lines 49-69: I find it odd that you are interjecting more literature review here as opposed to providing it earlier in the document.

Response: As commented before more references are added in the beginning of the document

Line 63: missing comma... "... storm characteristics, a regional model..."

Response: Yes, Thank you is amended.

Line 65: can a resolution of 80 meters accurately capture terrain features and individual homes?

Response: Homes and small terrain features are not included in the grid resolution but flood walls were included by means of thin weirs in the model

Line 69/Figure 3: There is not enough contrast in this image to make out the details. The date/time codes for every storm report make the figure unnecessarily busy.

Response: Yes, some labels were removed and the figure was modify.

Line 73: what data sources did you use for land cover / land use to assign friction coefficients? (nb. Ignore this comment, I see the answer on line 99).

Response: See comments on line 99.

Lines 75-79/Table 1: how do these relate to the 80-meter resolution mentioned previously?

Response: As commented above, the intention is to compare different bathymetry/topography information data. Resolution of this information is variable from 500m (GEBCO) to 5m (IGN topography). The mesh of 80m can produce different results depending on the type of the information.

Our analysis consists of three domains because we implemented the model in domain decomposition mode, but this is not related to our analysis of the data resolution. For each DEM (GEBCO, IGN, IGN +Structures) we implemented that DEM in all of our domains.

Line 83: "... spatial resolution and temporal every 3hrs." awkward phrasing

Response: Ok, the sentence has been changed

Line 99: use of a constant Manning's "n" value for the entire grid is a significant technical weakness in this study. While it "may" be appropriate for some open water conditions, it is certainly not reflective of the terrain where the subject structures were likely found. Could you please provide a justification and suitable citation to support the use of a constant friction factor? I have read numerous papers in the past ten years that point to the importance of accurate representation of terrain roughness through the assignment of proper friction coefficients.

Response: We do agree that the roughness friction coefficients have an influence on the hydrodynamic results, particularly in places of shallow waters, but in order to simplify the analysis as was done in Tomiczek T., 2017, we decide to keep it constant. A small paragraph on the discussion is added regarding this topic.

Line 105: what is SHOM?

Response: A web link is added. Is an institute in charge of the monitoring of the north Atlantic bouys in front of the French and Spanish coast.

Line 105: "... during the whole simulation is good (Figure 4)." Is good relative to what? There is no quantitative basis for this statement.

Response: A table with the goodness of fit indicators is added. Also a small explanation on the reason by which the significant wave height is compared to the swell height is done.

Line 110/Figure 4: Can you please explain the spurious oscillation at the beginning of your simulation results? I incorrectly assumed that this was the surge event, but it appears to be a numerical instability associated with model spinup.

Response: Since at the time of the beginning of the simulation the water levels in the whole domain are unknown, it is common to set as 0 m.a.s.l the water elevation as initial condition. This produces the need to extend the simulation and start it before the day from which we want to make the analysis. How long is this period (or spin-up time) depends on the size of the domain and time interval of the simulation. In our case we start the simulation from the 20 of February of 2010 guaranteeing enough time for the model to adjust the tide values to the real ones.

Line 115/Figure 5: there is absolutely no assessment or narrative to accompany these results. Since wave properties are highlighted as one of your preferred explanatory

variables in the damage analysis, and since wave processes contribute to coastal flooding (your other explanatory variable), can you provide some commentary on the disagreement between the modeled and measured waves? Why are the observations listed as "swell height"? Are you comparing two different wave statistics in this figure (i.e., swell height and significant wave height)?

Response: Yes, thank you for this observation. An explanation is added both together with the goodness of fit indices for the waves and tides are added.

Line 121: "... specifically, relates the..." typo and awkward phrasing

Response: Ok, the sentence has been changed.

Line 127: missing commas after "paper" and "way"

Response: Ok, the sentence has been changed.

Lines 132-138: Damage curves are often given for different levels/magnitudes of damage. Here it appears that you are integrating the damage results across all of the discrete damage ratio increments. Was this a specific choice/preference, an artifact of your damage indicator scheme, or something else entirely? Was there no interest in disaggregating the damage data as is traditionally done in these types of analyses? For example, developing unique damage curves for different damage states?

Response: Unfortunately we do not have enough data to disaggregate.

Line 133: I don't think "Box-Whisker" is capitalized, not proper nouns

Response: Thank you for the observation.

Line 136: "Damage" should not be capitalized

Response: Thank you for the observation.

Line 142: "Where" should not be capitalized since you are using the equations as the subject of your sentence.

Response: Thank you for the observation.

Line 145/Figure 6: I find these figures to be less helpful than I had hoped. The size (small) and contouring scheme do not allow for much interpretation of the results.

Response: Figure 6 is changed modifying the colours, the legend and making a zoom over the simulation domain.

Line 150: "Similarly" -> "Similar"

Response: Thank you for the observation

Line 152/Figure 7: at the scale provided it is difficult to discern details in these figures. Also, there is no explanation of the symbols in these figures.

Line 157: "related with the" -> "related to the"

Response: Thank you for the observation

Line 160/Table 2: For explanatory values (cf Table 2) used in Eq 2, how were means and standard deviations evaluated for combinations of variables that do not necessarily vary consistently in time? In other words, did you estimate the time-variation of each variable group/combination and then take the mean and standard deviation of the entire time-series? Or, did you evaluate the mean/stdev of each individual parameter and then form the variable groups?

Response: For every single claim at the Ile du Re and surroundings the maximum hydrodynamic variables were extracted at every single location. In this way the time series of the simulations are restricted for the maximum values that reach every single variable. A short line explaining this is added in the damage curve section.

Line 164: typesetting of "hsig" -> "Hsig"

Response: Thank you for the observation.

Line 207: delete comma after point

Response: Thank you for the observation.

Line 215: "... as thin or concrete structures like flood walls at typically only a few 10's of centimeters thick, and so do not appear in digital elevation models." Awkward phrasing.

Response: Yes, the phrase is adjusted.

Lines 215-220: what about errors/uncertainty in your model predictions?

Response: Thank you for the comment. It was added along the document at the meteorological and damage functions some paragraphs about the uncertainty coming from the hydrodynamic modelling and from the claims data itself in the document.

I commend the authors on a very strong first draft of what I'm sure was a very challenging manuscript to prepare. The authors are absolutely on track towards having a very strong publication that will productively add to the body of literature on damage to coastal structures during extreme events.

Sincerely,

Bret Webb

Response: We certainly acknowledge your comments on the document, thank you for reading the document and give your feedback. We hope the present version is more accurate.

Andres et al.,