

Review and Comments on se-2021-118

Anonymous Referee #1

Referee comment on "Interdisciplinary fracture network characterization in the crystalline basement: a case study from the Southern Odenwald, SW Germany" by Matthis Frey et al., Solid Earth Discuss., <https://doi.org/10.5194/se-2021-118-RC2>, 2021

General Review

The manuscript proposes an extensive structural study of the Tromm Granite with various approaches: lineament analysis, LiDAR implemented on outcrops, DFN model, gravity and radon measurements. The manuscript is written in understandable manner and identify potential targets for future geothermal projects in the Odenwald area. An effort should be done in the description of the methodology in order to clarify for which purpose the different approaches were chosen and how they contribute to the final interpretation.

The main issue of this interdisciplinary study is the comparison of results from different scales that sometimes is not relevant. To be clear, using data at the regional scale or at the outcrop scale to interpret geothermal circulations in a deep reservoir is not trivial. For example, they work with radon measurements and Bouguer anomaly implemented on an outcrop to interpret permeability of fault zones. The interpretation of gravity data in term of permeability is very smooth and large scale. It is more adapted for permeability at regional scale than a reservoir one as suggested in the manuscript. Furthermore, interpretation of permeability of a fault zone observed on an outcrop can not be directly transferred to the reservoir. What geomechanically happen if the fault observed on the outcrop is buried several km deep? We know from reservoir studies that the permeability of the fault zone can be modified if they are critically stressed. Did past-circulations occurred in these faults? If yes, what is the nature of the fluid? Are they opened, sealed or healed fault zone? These are questions that should at least be mentioned.

They propose to apply their results for a future geothermal project in the Odenwald area and often mentioned the projects in operation of the URG as example. However, they forgot to really confront their results to observations made in the URG when they define the ideal targets for geothermal projects (comments 9, 14, 16 and 18). Moreover, when you conduct a geothermal prospection, you cannot ignore the thermal data of the area, that is not even mentioned in the study.

I can only recommend this manuscript for publication after moderate revisions suggested below that the authors may want to consider when improving their paper.

Specific Comments

Comment 1: L28 Exploration, therefore, began already in the 1980s, allowing to build on

decades of experience (Reinecker et al., 2019; Cuenot et al., 2008; Dezayes et al., 2005a)

Please check also references

Genter et al. 2010, C.R. Geosci. Doi:10. 1016/j.crte.2010.01.006.

Schill et al., 2017, Geothermics, Doi: 10.1016/j.geothermics.2017.06.003.

Comment 2: L30 Convective heat transport along active large-scale fault zones has been identified as the main reason for the elevated temperatures at reservoir depths of 2 to 4 km (Baechler et al., 2003; Baillieux et al., 2013; Guillou-Frottier et al., 2013; Duwiquet et al., 2021)

Please rephrase this sentence. The thermal gradients below 1km depth is 5°C/km in Soultz and Rittershoffen wells and almost null below 2km in Bruchsal, Landau, Cronenbourg wells. Thus, between 2 and 4km depth, the temperature does not increase so much. The temperature increases anomalously in the shallow part of the sedimentary cover.

Comment 3: L45-50

The authors seem not to be aware that borehole imaging are rarely investigated alone. At the borehole scale, gamma ray and cuttings samples are almost always available in deep wells and they inform about the mineralogy and alteration petrography very precisely. These informations are correlated to the structural ones from borehole imaging. Besides looking mineralization observed on an outcrop cannot be simply transposed to the reservoir. Temperature and pressure vary very quickly from a fracture to another one and influence the minerals deposition within. Please nuance your affirmations.

Comment 4: L133 c. 20 × 30 m

I don't understand how a pixel cannot be a square. Why do you use 2 DEMs and not only the high resolution one?

Comment 5: paragraph 3.1.2

Where are the results of the automatic plane recognition? Why did you manually interpret the data besides the automatic interpretation? Do the results differ? Is Figure 3b the result of the calculation described L155? If yes please refer in the text. I find the methodology section for the LiDAR data very confusing and don't really understand for which purpose are made the different treatments of the data. Please clarify this section.

Comment 6: is significantly higher than the amount of mapped faults

Do you mean significantly "higher" than?

Comment 7: 177 for SRTM and 471 for the 1m DEM

The 177 lineaments from SRTM are also observed and counted in the 471 with the 1m DEM?

Comment 8: figure 4 (b) regional analysis using SRTM data (20 x 30 m resolution) (adapted from van Zyl, 2001); (c) local analysis using 1 m DEM (adapted from HVBG, 2021).

From the paragraph 3.1.1, I understood that you inspected the lineaments with QGIS. On figure 4b, you mention "adapted from van Zyl". A SRTM is a free data, so what did you adapt from this reference? I guess HVGB gave you the 1m DEM of 4c, but only the raw data or also an interpretation of the lineaments? What did you do really on the figure 4? Please clarify.

Comment 9: L340 the mean permeabilities of 340 the granitic basement range from $1E-17$ to $1E-15$ m² (Egert et al., 2020; Mahmoodpour et al., 2021 in prep.)

Please add the value for the permeability in the fault from Baujard, C. et al. 2017 (Geothermics, doi:10.1016/j. geothermics.2016.11.001).

Comment 10: L371

Fig 10 is called before Fig 9

Comment 11: L396-398

Do you have a reference from literature for this affirmation or it is something you observed on the field?

Comment 12: L418 Contrary to this, the fracture sets of the two outcrops Hammelbach and Weschnitz Valley are more influenced by local fault zones.

Do you have a reference for the direction of the local fault zones in the area or do you hypothesize that they are striking between N50°E and N130°E and thus, influence the sets of the two outcrops? Please clarify

Comment 13: plannend

Correct with "planned"

Comment 14: L466 This observation suggests that the fault core does not show increased permeability compared to the damage damage zone (Caine et al., 1996), e.g. due to mineralization, which also explains the positive gravity anomalies.

Please delete one "damage" of your sentence.

Correlation between acoustic logs and hydraulic tests in GPK-1 at Soultz reveals that the fluid flow is channelized in the core of the fracture zone. (Evans, K., Genter, A., Sausse, J., 2005. *J. Geophys. Res.* doi:10.1029/2004JB003168.) In the model of Caine et al. (1996), the permeability of the core is directly linked to the nature of the mineralization. Quartz is associated with a high permeability whereas, occurrences of clays tend to reduce the permeability. Did you observe the mineralization of the studied fault zone?

Comment 15: On the one hand, the granitic body has a similar mineralogical composition as the reservoir rocks e.g. in Soultz-sous-Fore^{ts} or Rittershoffen (Dezayes et al., 2005b).

Please for the mineralogical composition of Soultz, cite " Traineau, H., Genter, A., Cautru, J.-P., Fabriol, H., Chèvremont, P., 1992. Petrography of the granite massif from drill cutting analysis and well log interpretation in the geothermal HDR borehole GPK-1 (Soultz, Alsace, France). In: Bresee, James C. (Ed.), *Geothermal Energy in Europe – The Soultz Hot Dry Rock Project*. Gordon and Breach Science Publishers, Montreux, Switzerland, pp. 1–29."

and Rittershoffen cite "Vidal et al., 2018, *JVGR*, doi : 10.1016/j.jvolgeores.2017.10.019 »

Comment 16: L475 Consequently, the orientation and density of fractures in the deep boreholes can assumed to be similar to the Odenwald values.

Which deep boreholes? The orientation E-W observed at the North of the Tromm Granite is not a predominant set of the deep wells in the URG.

Comment 17: L486 which fits well with observations from Soultz sous Forets (Egert et al., 2020; Sausse et al., 2010)

Please correct "observations"

Please cite Evans, K., Genter, A., Sausse, J., 2005. J. Geophys. Res. doi:10.1029/2004JB003168. Inside the paper, it is described that in GPK-1, 95% of the flow entered the rock mass at 10 discrete flow points over more than 500 fractures detected in image logs.

Comment 18 L488 The deviated open-hole sections should preferably be oriented perpendicular to the fracture set with the highest permeability, thus intersecting as many of them as possible, allowing for high flow rates.

This is not observed at Rittershoffen. The well GRT-2 presents the highest flowrate of the URG and the trajectory of the well is N-S inside the Rittershoffen fault zone that strikes N-S. The well and the fault are parallel, but the well was drilled inside the fault zone that maximize the connection between well and permeable fracture network associated to the fault. Please check the results of the references you cited "Baujard et al., 2017" and "Vidal et al., 2017" and nuance your affirmation in your manuscript.

Comment 19 L491 Controlling induced seismicity

Please rephrase, because you cannot "control" seismicity, maybe you mean minimize?

Comment 20 L493 Stimulation is generally more feasible in areas with higher natural permeability

Please rephrase, because if natural permeability is high, you don't need to stimulate.

Comment 21 Geothermal prospection is also based on the temperature data. You can always try to enhance the hydraulic properties of your reservoir with EGS technology, but the temperature is something you cannot modify so you need to secure this parameter during your exploration study.

Comment 23 L528 Structural investigations and gravity anomalies show that the most suitable hydraulic properties are expected at the margin of the granitic pluton, where faults of regional extent influence the fracture network.

During the cooling of a granitic pluton, the margins are more affected by circulations of the residual fluids and thus, more altered than the center. The altered zones are preferential pathways for further circulations of the geothermal resource.

Comment 24 L530 Granite constitutes a relatively intact basement with significantly lower permeability, where permeability could only be created artificially by stimulation measures for geothermal utilization.

You cannot create permeability artificially with stimulation. Stimulation is for enhancing existing natural permeability. Fracturation can "create" the permeability but in the case of the URG, this technique is not appropriate because induced seismicity in urbanized areas

generally lead to the end of the geothermal project.

Technical Comments Please check comments 6, 10, 13, 14 and 17